




40W Triple Output Series - with approval



- Universal AC input / full range
- High reliability
- Approvals: ETS/LVD/EMC/ CE
- 100% full load burn-in test
- Protections: overload/ over voltage/ short circuit
- V1 is isolated from the other outputs
- 2 years warranty
- F603 129 x 98 x 40(mm)

AC input voltage range 85~264VAC (120~370VDC)
 Inrush current cold start, 20A/115V, 40A/230V
 Input leakage current < 0.7mA/ 230VAC
 Line regulation (full load) ≤ ± 0.5%
 Load regulation V₁: ≤ ± 0.5%, V₂,V₃: ≤ ± 1% (with regulators);
 ≤ ± 6% (without)
 Output voltage adjust range V₁: ± 5% of rated output voltage
 Output overload protection 110~150%
 Output over voltage protection 115~150%
 Withstand voltage I/P-O/P: 3.0KVAC/1min; I/P-F/G: 1.5KVAC/1min
 O/P-F/G: 0.5KVAC/1min
 Rise, Hold up time 50ms, 20ms@full load (typical)
 Operating temp. & humidity -10°C~+50°C, 20%~93%RH (non condensing)
 Storage temp. & humidity -20°C~+85°C, 20%~95%RH (non condensing)
 Safety standards GB4943, UL60950, EN60950
 EMC standards GB9254, EN55022 classB, EN55024
 EN61000-3-2,3, EN61000-4-2,3,4,5,6,8,11
 Cooling method convection

- High reliability
- 100% full load burn-in test
- 2 years warranty

< 0.5mA/ 230VAC
 ≤ ± 0.5%
 V₁: ≤ ± 0.5%, V₂,V₃: ≤ ± 1%
 ≤ ± 6% (without)
 V₁: ±

°C~+50°C
 °C~+85°C

Model	DC Output		R&N	Efficiency
	V	I		
HF40W-TL-A	5V	0.5~4.0A	50mV	68%
	12V	0.2~1.0A	100mV	
	-12V	0.2~0.7A	100mV	
HF40W-TL-B	5V	0.5~4.0A	50mV	69%
	15V	0.0~1.0A	100mV	
	-15V	0.1~1.0A	100mV	
HF40W-TL-C	5V	0.5~4.0A	50mV	68%
	12V	0.2~1.5A	100mV	
	-5V	0.2~1.5A	80mV	

Drawing

