



www.powersupply-cn.com

### Feature:

Constant voltage  
Outdoor LED Power Supply  
PWM switch design  
Input rated frequency: 50 or 60Hz  
Input frequency range: 47 to 63Hz

Size: 217 x 28.5 x 20mm  
Net weight: 250g

### Efficacy:

Efficiency: 80% Min  
Output Line Regulation:  $\pm 3\%$   
Output Load Regulation:  $\pm 5\%$   
Output Over Shoot: 10% Max

# AG

## Electrónica S.A. de C.V.

Model No.	Input Voltage	Output Voltage	Output Current	Output Power
VA-05020M	170 - 250VAC	5VDC	4A	20W
VA-10030M	170 - 250VAC	10VDC	3A	30W
VB-12030M	90 - 130VAC	12VDC	2.5A	30W
VA-15030M	170 - 250VAC	15VDC	2A	30W
VA-18030M	170 - 250VAC	18VDC	1.6A	30W
VA-24030M	90 - 130VAC	24VDC	1.25A	30W

Electrónica S.A. de C.V.

República del Salvador N.20 Segundo Piso

Tel. 5130 - 7210

Short Circuit Protection, Over Load Protection, Over Voltage Protection (recover automatically).

Over Thermal Protection, Thunder proof Protection (recover automatically).

Completely air proof, achieve waterproof rate IP 68.

Test:

Visita las notas de aplicación en:

[http://www.agelectronica.com/notas/Nota1/Nota\\_1.htm](http://www.agelectronica.com/notas/Nota1/Nota_1.htm)

Completely air proof, achieve waterproof rate IP68.

Dielectric Withstand Voltage: 1.5KV/3mA/60s

Acotación:

mm

Tolerancia:

Tolerancia:

[www.agelectronica.com](http://www.agelectronica.com)

Escala

Rev 1. JSM

Rev 2.

**LED FUENTE DE PODER 12V 2.5A 30W**

Fecha:

22/FEB/10

Número de parte AG

**VB-12030M**

# AG

*Electrónica S.A. de C.V.*