

**Features:**

Constant voltage
Outdoor LED Power Supply
PWM switch design
Input rated frequency: 50 or 60Hz
Input frequency range: 47 to 63Hz

Max. Output power: 60W
Size: 180 x 68 x 53mm
N.W.: 800g

Efficacy:

Efficiency: 80% Min
Output Line Regulation: $\pm 3\%$
Output Load Regulation: $\pm 5\%$
Output Over Shoot: 10% Max

Model No.	Input Voltage	Output Voltage	Output Current
VA-05045P	170 – 250VAC	5VDC	0□9A
VA-10060P	170 – 250VAC	10VDC	0□6A
VB-12060P	90 – 130VAC	12VDC	0□5A
VA-15060P	170 – 250VAC	15VDC	0□4A
VB-12100D024	90 – 130VAC	12VDC	0□8.4A

Protection:

Short Circuit Protection, Over Load Protection, Over Voltage Protection (recover automatically),
Over Thermal Protection, Thunder proof Protection (recover automatically)
Completely air proof, achieve waterproof rate IP 68.

Test:

100% full load burn-in test
Completely air proof, achieve waterproof rate IP68.
Dielectric Withstand Voltage: 1.5KV 3mA 60s

Visita las notas de aplicación en:
http://www.agspecinfo.com/notas/Nota1/Nota_1.htm

Electrónica S.A. de C.V.

	AG Electrónica S.A. de C.V. República del Salvador N.20 Segundo Piso Tel. 5130 - 7210		
	Acotación: mm	www.agelectronica.com	Escala
Tolerancia:	FUENTE CONMUTADA 12V 5A 60W		
Tolerancia:	Fecha: 22/FEB/10	Número de parte AG VB-12060P	