

VB-12150T (ultima)

Photo	Size (mm)	Certificate	housing material	Model Number	Weight	AC input voltage range	Max. output power	Output voltage	Max. output electrical current	Connect the line request
	L201×W25.5×H26.5(mm)	CE	Aluminum	JL-2415A	174g	110-250V	15W	24V±0.5V	0.625A	The wire of VDE(200mm).
				JL-1215A	174g	110-250V	15W	12V±0.5V	1.25A	
	L201×W25.5×H26.5(mm)	CE	Aluminum	JL-1220A	246g	90-250V	18W	12V±0.5V	1.5A	the wire of VDE(200mm)
				JL-2420A	246g	90-250V	18W	24V±0.7V	0.75A	
	L220×W30×H20(mm)	CE	Aluminium	VA-12030M	248g	170-250V	30W	12V±0.5V	2.5A	the wire of VDE(200mm)
				VA-15030M	248g	170-250V	30W	15V±0.5V	2A	
				VA-18030M	248g	170-250V	30W	18V±0.5V	1.6A	
				VA-24030M	248g	170-250V	30W	24V±0.5V	1.25A	
				VA-05020M	248g	110-250V	20W	5V±0.5V	4A	
				VB-12030M	248g	90-130V	30W	12V±0.5V	2.5A	No CE
	L122×W58×H25 (mm)	CE	Aluminium	VA-12020X	280g	170-260V	20W	12V±0.5V	1.67A	the wire of VDE(200mm)
				VA-24020X	280g	170-260V	20W	24V±0.5V	0.83A	
	L252×W40×H22 (mm)	CE	Aluminium	VA-05030D006	408g	170-250V	30W	5V±0.5V	6A	the wire of VDE (200mm)
				VA-12040D006	408g	170-250V	40W	12V±0.5V	3.3A	
				VA-24040D006	408g	170-250V	40W	24V±0.5V	1.6A	
	L180×W68×H53(mm)	CE	Aluminium	VA-10060P	850g	170-250V	60W	10V±0.5V	6A	the wire of VDE,output with two 18#×2C (200mm)
				VA-12060P	850g	170-250V	60W	12V±0.5V	5A	
				VA-15060P	850g	170-250V	60W	15V±0.5V	4A	
				VA-24060P	850g	170-250V	60W	24V±0.5V	2.5A	
				VB-12060P	850g	90-130V	60W	12V±0.5V	5A	
	L205×W132×H65 (mm)	CE	Aluminium	VA-12100T	2000g	170-250V	100W	12V±0.5V	8A	the wire of VDE,output with three groups 18#×2C(300mm), one input(300mm)
				VA-24100T	2000g	170-250V	100W	24V±0.5V	4A	
	L235×W132×H65 (mm)	CE	Aluminium	VA-12150T	2350g	170-250V	150W	12V±0.5V	12.5A	the wire of VDE,output with four groups 18#×2C (500mm), one input (300mm)
				VA-24150T	2350g	170-250V	150W	24V±0.5V	6.25A	
				VA-05100T	2350g	170-250V	150W	5V±0.5V	20A	
				VB-12150T	2350g	90-130V	150W	12V±0.5V	12.5A	
		No CE								